



CONTINUOUS VERTICAL CONVEYOR QUOTATION WORKSHEET

Company _____ Date _____
Contact _____ Quote Due _____ Desired Delivery _____
Phone _____ No. _____ Contact Email _____ State _____
Sales Contact _____ Quote # _____
Quantity _____

Product Information:

Max. Length _____ Max. Width _____ Max. Height _____
Min. Length _____ Min. Width _____ Weight _____
Description of Conveying Surface (Bottom) of Item: _____

Lift Requirements:

Loading Elevation: _____
Unloading Elevation: _____
Required Thruput in Items per Minute: _____ / minute
Required Chain Speed: _____ FPM

Service Required:

☐ Up ☐ Down ☐ Reversing

Plant Voltage:

☐ 110V Single Phase ☐ 220V Three Phase ☐ 575V/60 Hz Three Phase (Canadian)
☐ 220V Single Phase ☐ 440V Three Phase ☐ Other: _____ (Specify)

Control Voltage:

☐ 24V DC ☐ 10V AC

Control Panel By: ☐ OAL ☐ Customer
Infeed Conveyor By: ☐ OAL ☐ Customer
Discharge Conveyor By: ☐ OAL ☐ Customer

Options:

- | | |
|--|--|
| ☐ Dodge bearings _____ | ☐ Torque Slip Monitor |
| ☐ Standby drive _____ | (Additional control logic required) |
| ☐ Central grease points | ☐ Other: _____ |
| ☐ Service platform (36" wide) | _____ |
| ☐ Specific drive brand | _____ |
|
 | |
| ☐ _____ | |
| ☐ Specific brand of sensors | |
| _____ | |
|
 | |
| ☐ C-face reducer with coupling mount | |
| and (2) SS (Automotive) | |
| ☐ Brad Harris type cords and multiple | |
| pin connectors @ J-box (Automotive) | |
| ☐ Drip pan under drive | |
| ☐ Clean out/access panels | |
| ☐ Cottered chain instead of riveted | |
| ☐ Extra manuals; Qty. = _____ | |

Approval Drawing Required: ☐ Yes ☐ No