

RECIPROCATING VERTICAL CONVEYOR QUOTATION WORKSHEET

Company _____ Date _____
 Contact _____ Quote Due _____ Desired Delivery _____
 Phone No.: _____ Contact Email: _____ State _____
 Sales Contact: _____ Quote #: _____
 Quantity: _____

Product Information:

Max. Length _____ Max. Width _____ Max. Height _____
 Min. Length _____ Min. Width _____ Weight _____
 Description of Conveying Surface (Bottom) of Item: _____

Description of CDLR in RVC (Must have side mount high drive): _____

Lift Requirements:

Loading Elevation: _____
 Unloading Elevation: _____
 Required Thruput in Items: _____ / minute, _____ / hour

Configuration:

☐ "C" Type ☐ "Z" Type ☐ 90° ____ ☐ "I" Type

Service Required:

☐ UP Service ☐ DOWN Service ☐ Reversing

Plant Voltage:

☐ 110V Single Phase ☐ 220V Three Phase ☐ 575V/60 Hz Three Phase (Canadian)
☐ 220V Single Phase ☐ 440V Three Phase ☐ Other: _____ (Specify)

Control Voltage:

☐ 24V DC ☐ 110V AC

Brake Voltage: _____

Control Panel By: ☐ OAL ☐ Customer

Infeed Conveyor By: ☐ OAL ☐ Customer

Discharge Conveyor By: ☐ OAL ☐ Customer

Options:

- | | |
|--|--|
| ☐ Dodge bearings | ☐ Extra manuals; Qty. = _____ |
| ☐ Standby drive | ☐ Electrical interlock for maintenance pins _____ |
| ☐ Central grease points | (Additional control logic required) |
| ☐ Specific brand of sensors | ☐ Other: _____ |
| _____ | _____ |
| ☐ Drip pan under drive _____ | _____ |
| ☐ Cottered chain instead of riveted _____ | _____ |

Approval Drawing Required: ☐ Yes ☐ No